

CHS-Series specification

Model		CHS-01S	CHS-01D
Material to be Used		PE/PP PVC	PE/PP
Product			
Product Volume (Min/Max)	cc	20-200	20-100
Product Dia. (Min/Max)	mm	15~100	10-60
Product Max. Weight	g	60	30
Extruder			
Screw Diameter	mm	42	42
L/D		1:22	1:22
Screw-speed Range (PE/PP)	RPM	15-85	15-85
Screw-speed range (PVC)	RPM	10-60	X
Extruding VS Motor	HP	7.5 7.5	7.5
Max. Extruding Output /per Hour	kgs	10 12	10
Barrel Heating Zone	zone	2	2
Barrel Heating Capacity	kw	3	3
Die Head			
Twin Cavity Center Distance	mm	X	100
Heating Zone	Zone	3	3
Heating Capacity	kw	1.6	3.6
Mold Platen			
Max. Opening Stroke	mm	230	230
Min. Clamping Stroke	Mm	85	85
Hydraulic System			
Pump Motor		5HP×6P	5HP×6P
Pump Pressure	Kg/cm	140	140
Oil Tank Capacity		30	30
Total Power Consumption	kw	12 15	14
Machine Weight	ton	1.5	1.5
Packing Size (L*W*H)	inch	79" ×89" ×69"	79" ×89" ×69"
Machine Meas' t	M	8	8